

5-10T

柴油平衡重式系列叉车 5-10T Counterbalance Diesel Powered Forklift Truck



- 1.动力强劲
Powerful Engine

可选配：日本五十铃发动机、珀金斯发动机
Engine For Optional:Chaochai6102-BG、Isuzu 6BG1、Perkins 1104D-44TA(EURO III)
- 2.液力变速箱
Hydraulic Gear-box

3.双前轮
Double Front Wheel

4.液压转向桥
Hydraulic Turning Bridge
- 5.可选配高档减震座椅
Optional top-grade damped seat

主要技术参数 Main Specification

型号		MODEL	CPCD50	CPCD60	CPCD70	CPCD80	CPCD100	
额定起重量Load capacity			kg	5000	6000	7000	8000	10000
载荷中心Load center			mm	600	600	600	600	600
动力形式Power type								
最大起升速度(满载)Max. lifting speeds(with load)			mm/s	470	470	450	350	310
最大行驶速度(满/空载)Max. driving speeds(with/without load)			km/h	21/23	21/23	21/23	18/25	16/22
最大牵引力(满/空载)Max.towing(with/without load)			kN	52	53	54	57	58
爬坡度(满/空载)Gradeability(with/without load)			%	20/25	20/25	20/25	19/20	19/20
H1起升高度Lifting height			mm	3000	3000	3000	3000	3000
自由起升高度Free lift			mm	150	150	150	150	150
门架倾角(α前/β后)Tilting angles(forward-backward)			°	6/12	6/12	6/12	6/12	6/12
最小转弯半径Min.truning radius			mm	3430	3430	3450	3700	4000
最小直角通道宽Min. right angle aisle width			mm	3090	3090	3090	3310	3540
最小离地间隙Minunder-clearance			mm	230	230	230	250	250
Dimensions 外形尺寸	A全长(含货叉)Overall length(including fork)		mm	4760	4760	4850	5160	5500
	B全宽Overall width		mm	1995	1995	1995	2165	2275
	H全高(门架缩进)Overall height(mast lowered)		mm	2500	2500	2500	2700	2850
	H2作业高度(门架全伸出)Overall height(mast extend)		mm	4420	4420	4420	4375	4300
H3至护顶架高度Overall height to overhead guard			mm	2420	2420	2420	2585	2585
A1前悬距Fork overhang			mm	630	635	610	700	720
A2轴距Wheel base			mm	2250	2250	2250	2500	2800
Tread 轮距	B1前轮Front tread		mm	1470	1470	1470	1600	1600
	B2后轮Rear tread		mm	1700	1700	1700	1700	1700
Tyre 轮胎	前轮Front tyre			8.25-15-14	8.25-15-14	8.25-15-14	9.00-20-14	9.00-20-14
	后轮Rear tyre			8.25-15-14	8.25-15-14	8.25-15-14	9.00-20-14	9.00-20-14
自重Total weitht			kg	8200	8640	9500	10960	12510
B3货叉宽度Fork width			mm	150	150	150	170	175
H4货叉厚度Fork thickness			mm	55	60	65	70	80
挡货架高Backrest height			mm	1365	1365	1365	1374	1015
A3标准货叉长度Fork length			mm	1220	1220	1220	1220	1220
Engine 发动机	型号Engine model		国Ⅲ ChinaⅢ					
	额定功率Rate power		kW	66	66	66	92	92
	额定功率时转速Rotate speed at rate power		rpm	2200	2200	2200	2200	2200
	最大扭矩Max.torque		Nm	350	350	350	480	480
	最大扭矩转速Rotate speed at max torque		rpm	1600	1600	1600	1700	1700
	备注Note		根据用户需求可选装国产全柴、锡柴、及进口五十铃、洋马、珀金斯等型号发动机 Optional China Quanchai Xichai Japan ISUZU, UK Perkins engine and so on.					
变速形式Type of power shift			液力Tor-con					

