

20-35Y

越野叉车 20-35Y Rough Terrain Forklift Truck



- 1.标配警示灯、后照大灯
Warning light Rear light

2.双级空气过滤
Dual air filter
- 3.超宽超强视野门架
Wider and better mast view

4.深花纹大宽度越野轮胎
Deep and wide-width off-road tire

主要技术参数 Main Specification

型 号Model	CPCD20Y/25Y/30Y/35Y						
额定起重量 Rated Capacity (kgs):	2000/2500/3000/3500	外形尺寸 Dimensions:	全长 (含货叉)Total Length(including fork)mm:	4010/4010/4260/4260	自重 Self-weight kgs:		3950/4200/4700/4950
载荷中心 Load Center (mm):	500		全宽 Total Width mm:	1565/1565/1620/1620	货叉宽度 Fork Width mm:		122/122/125/125
动力形式 Power Type:	柴油 Diesel		全高 (门架缩进) Total Height (mast lowered) mm:	2280/2280/2320/2320	货叉厚度 Fork Thickness mm:		40/40/45/45
最大起升速度 (满载) Max. Lifting Speeds(with load) mm/s:	550/545/440/440		作业最大高度 (门架全伸出)Max. Height (mast extended) mm:	4065/4065/4270/4270	挡货架高 Backrest Height mm:		1000/1000/1230/1230
最大行驶速度 (满 / 空载)km/h Max. Driving Speeds(with/without load) km/h:	19.5/19.5/21/21 21/21/23/23	地面到护顶架高度 Height to Overhead Guard mm:		2270/2270/2315/2315	标准货叉长度 Standard Fork Length mm:		1070/1070/1220/1220
货叉起升高度 Fork Lifting Height (mm):	3000	前悬距 Front Overhang mm:		550/550/590/590	发动机 Engine	型号 Model:	国 III China III
门架倾角 (前倾 / 后倾)(°): Mast Tilting Angle (forward-backward):	6/12	轴距 Wheel Base mm:		1800/1800/1850/1850		额定功率 KW Rated Power:	36.8/36.8/48/48
最小转弯半径 Min. Turning Radius(mm):	2950/2950/3000/3000	轮距 Tread	前轮 Front Wheel mm:	1240/1240/1250/1250		额定功率时转速 Rotate Speed at Rated Power rpm:	2500/2500/2300/2300
尾部离去角 Departure Angle(°):	32/32/30/30		后轮 Rear Wheel mm:	1175		最大扭矩 Max. Torque Nm:	185/185/250/250
车架中部最小离地间隙 Min. Ground Clearance(mm):	290/290/320/320	轮胎 Tire	前轮 Front Tire:	12-16.5-14/12-16.5-14/ 14-17.5-14/14-17.5-14		最大扭矩时转速 Rotate Speed at Max. Torque rpm:	1800/1800/1800/1800
			后轮 Rear Tire:	27*10-12	变速形式 Power Shift Type:		液力 Tor-con

属具



可 选 配 置 表		
FR系列 1.5-4吨 柴油叉车	可选配置	驾驶室，双前轮，实心轮胎，高档座椅，高位排气，中位排气，倾斜缸、起升缸护套，双空气滤清器，油滤式空气滤清器，灭火器，灭火罩，A490、C490、495、498柴油机，进口五十铃4JG2、三菱4G64及LPG系统，二级全自由门架，加高门架，三级全自由门架，加长货叉，石材专用货叉、加大散热器，附液压油（液力传动油）散热器、加宽货叉架
	可选属具	侧移器、调距叉、侧移调距叉、软包夹、纸卷夹、平包夹、纸箱夹、砖块夹、旋转器、旋转叉、倾翻叉、环卫叉、铲斗、载荷稳定器、单双托盘叉、圆木夹、轮胎夹、推拉器、化肥推出器、桶夹、串杆、起重臂
F系列5吨 柴油叉车	可选配置	驾驶室，双前轮，实心轮胎，高档座椅，倾斜缸、起升缸护套，双空气滤清器，油滤式空气滤清器，灭火器，灭火罩，二级全自由门架，加高门架，三级全自由门架，加长货叉，石材专用货叉、加宽货叉架
	可选属具	侧移器、调距叉、侧移调距叉、软包夹、纸卷夹、平包夹、旋转器、旋转叉、圆木夹、轮胎夹、桶夹、串杆
F系列 7-10吨 柴油叉车	可选配置	驾驶室，实心轮胎，高档座椅，倾斜缸、起升缸护套，双空气滤清器，油滤式空气滤清器，灭火器，灭火罩，五十铃6BG1柴油机、加高门架，三级全自由门架，加长货叉
	可选属具	侧移器、软包夹、纸卷夹、旋转器、圆木夹、轮胎夹、串杆

OPTIONAL CONFIGURATION LIST		
FR Series 1.5-4Tons Forklift Truck	Optional Configuration	Cab with fan, Heater in the cab, Dual front wheel, Solid tires, High-grade seat, High exhaust, Median exhaust, Tilting and lifting cylinder sleeve, Dual air filter, Oil type air filter, Fire extinguisher bottle, Fire cover, A490BPG/ C490BPG/495BPG/498BPG diesel engine, EUR II JAPAN ISUZU 4JG2PE-01 engine, JAPAN Mitsubishi 4G64 engine and LPG system, 2-stage mast with full-free lift, Special higher mast, 3- stage mast with full-free lift, Lengthen fork, Special fork for stone factory, Special-big radiator, Radiator for transmission oil, Widen fork arm carrier.
	Optional Attachments	Side shifter, Fork positioner, Side shift and fork positioner, Bale clamps, Paper roll clamps, Flat bag clamps, Carton clamps, Block clamps, Rotator, Rotating clamps, Hinged fork, Sanitation fork, Bucket, Load stabilizers, Single double pallets handlers, Log holder, Tyre clamps, Push/Pull, Fertilizer throw-out, Drum clamps, Carpet boom, Cargo boom.
F Series 5Tons Diesel Forklift Truck	Optional Configuration	Cab with fan, Heater in the cab, Dual front wheel, Solid tires, High-grade seat, Tilting and lifting cylinder sleeve, Dual air filter, Oil type air filter, Fire extinguisher bottle, Fire cover, 2-stage mast with full-free lift, Special mast, 3-stage mast with full-free lift, Lengthen fork, Special fork for stone factory, Widen fork arm carrier.
	Optional Attachments	Side shifter, Fork positioner, Side shift and fork positioner, Bale clamps, Paper roll clamps, Rotator, Rotating clamps, Log holder, Tyre clamps, Drum clamps, Carpet boom.
F Series 7-10Tons Diesel Forklift Truck	Optional Configuration	Cab with fan, Heater in the cab, Solid tires, High-grade seat, Tilting and lifting cylinder sleeve, Dual air filter, Oil type air filter, Fire extinguisher bottle, Fire cover, EURIII UK PERKINS 1104D-44TA engine, JAPAN ISUZU 6BG1-02 engine, Special mast, 3-stage mast with full-free lift, Lengthen fork.
	Optional Attachments	Side shifter, Bale clamps, Paper roll clamps, Rotator, Log holder, Tyre clamps, Carpet boom.